



Declaration of Performance

No.: FIN 020-5020

Version: 5

Product Name:

TopSafe Pro

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

FIN 020-5020

2. INTENDED USE

Flexible sheets for waterproofing – Reinforced bitumen sheets for roof waterproofing – Definitions and characteristics

3. MANUFACTURER, and, if applicable, AUTHORIZED REPRESENTATIVE

BMI Suomi Oy,
Jaakonkatu 2,
01620 Vantaa-FI

4. SYSTEM OR SYSTEMS AVCP

System 2+

5. HARMONIZED STANDARD or ETA

EN 13707:2004+A2:2009

6. NOTIFIED BODY(IES)

0809 Eurofins Expert Services Oy

Signed for and on behalf of the manufacturer by:

Olli Kuoppamäki Managing Director BMI Suomi Oy



At Espoo

26.3.2026

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s in point 7. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Note 1: This product does not contain asbestos or tar components

Note 2: In the absence of European harmonized test methods, national limit values for content and release of relevant substances, must be taken into account.

7. DECLARED PERFORMANCE

Essential Characteristics	Performance	Harmonized technical specification
External fire performance	Broof(t2)*	EN 13707:2004+A2:2009
Reaction to fire	Class F	
Watertightness	Pass	
Tensile properties force longitudinal	800 ± 200 N/50 mm	
Tensile properties force transverse	650 ± 150 N/50 mm	
Tensile properties elongation longitudinal	40 ± 15 %	
Tensile properties elongation transverse	50 ± 15 %	
Root resistance	NPD	
Resistance to static loading	NPD	
Resistance to impact	NPD	
Tear resistance* longitudinal	250 ± 100 N	
Tear resistance* transverse	NPD	
Joint strength longitudinal	NPD	
Joint strength transverse	NPD	
Durability Heat resistance after aging	80 °C	
Durability Flexibility after aging	-10/0 °C	
Pliability (Flexibility at low °t)	-20/-10 °C	
Dangerous substances	None	

NPD: No performance determined

*System:

Meets the requirement Broof(t2) on in EN 13501-5 described wood substrates.